



# ADVANCE RANGE C537

CATEGORIA	Lavastoviglie sottobanco
LINEA	ADVANCE RANGE
CESTO	500x500
DIMENSIONI	585x600x815h mm
FOCUS	

Professional dishwasher designed for washing glasses of various sizes and up to **18 plates (Ø max 395 mm)** per cycle, with a productivity of **720 plates/hour**. Equipped with the **ADVANCE** control panel with 4 wash cycles and an automatic drain cycle (with installed drain pump), it allows simple and precise use. The display shows tank and boiler temperatures, self-diagnosis messages, scheduled maintenance alerts, and machine status via the **SMART START** button, which changes color based on the active phase. The electronic board allows adjustment of wash and rinse times and temperatures, with activation of the **Thermostop** function to ensure optimal results. The standard **dual electric detergent and rinse aid dispenser** ensures maximum hygiene and savings, while the wash and rinse arms guarantee reliability and long service life. Structure entirely made of **AISI 304 stainless steel** with front-facing components for simplified maintenance.

**MODEL COMPLIANT WITH EN IEC 63136 :**  
 See the [performance chart](#).

CARATTERISTICHE	ADVANCE RANGE C537
Dimensioni - (mm) L - P - H	585x600x815h mm
n° cesti/ora - (+55°C)	max 40
H massima bicchiere	365 mm
Ø massimo piatto	395 mm
Teglie	GN1/1 (special basket required)
Resistenza vasca - Capacità vasca	2,6 kW - 22 l
Resistenza boiler - Capacità boiler	2,5 kW - 7,3 l
Potenza pompa	0,52 kW - 0,7 hp
Potenza totale / Corrente	3,12 kW - 16 A
Tensione alimentazione standard	230V1N - 50Hz
Alimentazione acqua consigliata	+55°C
Durezza acqua consigliata	7÷10 °f
Consumo acqua per ciclo (con pressione consigliata 2 BAR)	2,2 l
Dosatore regolabile di detergente e brillantante	STANDARD
<b>CORREDO STANDARD</b>	
Portaposate	2
Cesto per bicchieri dim.500x500x100mm	1
Cesto 18 piatti dim.500x500x100mm	1
<b>OPTIONAL</b>	
UNIKO display touch con sistema Wi-Fi e IKLOUD	-
Pompa di pressione installata 0,5Hp	●
Pompa di scarico installata 32W con Ecoclean	●
Doppia parete isolamento termoacustico +18mm	●
Filtri inox vasca	●
Sistema ad osmosi inversa	-
Cesto portateglie 4 posti dim.500x500x200mm	●
Cesto inclinato per calici da vino dim.500x500x170mm	●
Kit 4 piedini inox 50-70mm	●
Sistema di Apertura/Chiusura "SOFT Door"	●
Avvio Ciclo "SOFT Start"	●
"DOUBLE Load" Supporto Doppio Cesto	●

● Optional Installabile, - Optional non installabile

## C537

